

TEMPUS® AIR CT

1-6 Stations Controller



The module can control from 1 to 6 DC latching hydraulic valves. It can read one rain or flow meter sensor input.

The module communicates with Gateway (3G or Wi-Fi) receiving the irrigation programming and transmitting data detected by the sensor.

The module allows direct connection from smartphone / tablet via Bluetooth®.

LoRa™ controlled, IP68 battery operated controller to manage from 1 to 6 hydraulic valves. It can read one rain or flow meter sensor input.

SPECIFICATION AND FEATURES

- LoRa™ radio connection [868-868.6] MHz, 25mW
- 1,2,4 or 6 stations
- LoRa™ range up to 800 m
- Independent programming by station
- Watering schedule: daily, odd/even days, day interval, cyclic
- 4 irrigation windows per station
- Bluetooth® Smart 4.0 Low Energy
- Automatic and manual start from smartphone/tablet/pc
- Permanent memory
- Rain or flow meter sensor input
- Rain delay function from 1 to 15 days or permanent
- Remote management via MyToroTempus App and MyToroTempus.com Web Platform
- IP68 waterproof
- Power Supply 9V DC battery
- 9V Latching solenoid compatible
- Maximum wiring distance from CT module to solenoids: 300 m
- Operating Temperature: -20°C / 60°C

CONTROLLERS ARE BATTERY POWERED NO NEED FOR WIRING

Discover MyToroTempus App to monitor and control your TEMPUS® AIR SYSTEM



Free download at App Store or Google Play



Codification

Code	Description
TEMP-AIR-C1	Tempus® Air CT - DC Controller 1 Station
TEMP-AIR-C2	Tempus® Air CT - DC Controller 2 Stations
TEMP-AIR-C4	Tempus® Air CT - DC Controller 4 Stations
TEMP-AIR-C6	Tempus® Air CT - DC Controller 6 Stations



Clear station labelling to make the installation process easy and intuitive



Bracket for installation on top of a solenoid included



Waterproof wire connectors included

MANUAL



Battery not included