

# EURO-KEY

## Serviceable drippers



## FEATURES

- Serviceable dripper to allow easy system monitoring
- Lug-equipped base for dripper line stability
- Wide turbulent flow path providing greater resistance to clogging
- Durability and resistance over time to atmospheric agents and against corrosion phenomena due to fertigation
- Disc made with a soft material that guarantees a perfect adhesion to the dripper walls

## SPECIFICATIONS

- 3 Nominal flow rate: High, Medium, Low
- Made of anti-UV stabilized polypropylene
- Recommended operating pressure: 0.5 - 2.0 bar
- Inlet: 4 mm barbed coupling
- Male outlet with connection for Ø 3.5x6 mm microtube

## PERFORMANCE

| Code        | Disc Colour | Flow rate @ |          |          |
|-------------|-------------|-------------|----------|----------|
|             |             | 0,5 bar     | 1,0 bar  | 1,5 bar  |
| IT-DNK-LO-3 | White       | 2,6 l/h     | 3,7 l/h  | 4,4 l/h  |
| IT-DNK-ME-3 | Green       | 3,7 l/h     | 5,9 l/h  | 7,6 l/h  |
| IT-DNK-HI-3 | Blue        | 7,9 l/h     | 11,4 l/h | 14,2 l/h |



## Codification

| Code        | Description   |
|-------------|---|
| IT-DNK-LO-3 | EURO KEY Low Flow. Serviceable dripper with white disc    |
| IT-DNK-ME-3 | EURO KEY Medium Flow. Serviceable dripper with green disc |
| IT-DNK-HI-3 | EURO KEY High Flow. Serviceable dripper with blue disc    |

